

GPS+Glonass 4 in 1 CPND 5”



At a Glance:

1. 5 inch TFT touch screen, resolution: 800*480
2. CPU: SiRF Atlas V, 500MHz
3. Operating system: Microsoft Win CE 6.0 R3 version
4. Storage: 2G Mbytes NAND flash + 128 Mbytes DDR2
5. GPS/Glonass dual support
6. Functions: MP3/MP4, Photo and Ebook, GSM (SMS)/GPRS (Internet Connection), TRACKER/NAVIGATOR 4 in 1.
7. Antenna: internal high sensitivity antenna
8. Battery: with 1200 mAH Lithium polymer battery, up to 3hours
9. With 1W speaker
10. Dimension: 5.36"x3.5"x0.49"
11. Weight: 8.5oz

Model: V55G

5” Connected PND with GPRS, Glonass+ GPS Dual Support



Model: V551G



Model: V552G

I. Features:

1. 5" TFT LCD screen with touch panel, 800*480 support
2. GPRS connectivity, SMS and calling support
3. Dual-band GSM/GPRS 900/1800 MHz (850/1900MHz Optional)
4. Glonass and GPS dual support
5. Multimedia Player Support.
6. Boot up automatically if charger inserted
7. SIM card accessible easily ,through bottom side

II. Technical Specification:

Hardware		
CPU		ARM11 SiRF Atlas V, AT5501, 500MHz dual-core
Storage	Flash	Built-in Nand flash 2GB
	RAM	128MB DDR2 (128MB *1)
Display	Display	5" TFT LCD, brand Innolux, K&D, Hannstar
	Aspect Ratio	16:9
	Resolution	5" 800*480
Satellite Receiver		Navis : NV08C Glonass and GPS dual support TTFF: cold start 30s, warm start 9s, hot start 3s, under open sky
Antenna		Internal high sensitivity antenna
Input/Output	Touch Panel	4 wires resistive type touch panel
	Speaker	Built-in speaker 1W
	Headphone	2.5 mm Stereo Jack
	Extended storage	Micro SD card slot, up to 32GB
	Mini USB	Mini USB2.0, 10pin Hi speed, transfer up to 480 Mbps, support ActiveSync and Mass storage
Buttons / Switches		Power On/Off, sleep, Reset
LED Indicator		red for charging, green if fully, GSM indicator: blue flash
Battery		Non-removable rechargeable Li-Polymer battery, 1200mAh
RTC		Yes, supplied by lithium battery
Car Charger	Input	DC +12/24V
	Output	DC +5V, 1.5A, via mini USB
AC/DC Adapter (Optional)	Input	AC 110~240V
	Output	DC +5V,1.5A, via mini USB
SMS		Yes
Web Browser		Opera mini 5

GSM Module	Frequency	A8000 with dual-band GSM/GPRS 900/1800 MHz(850/1900MHz)	
	Certification	PTCRB ,CE, FCC, RoHS compliant and Local Type Approval	
Tracker		Locate /tracking for security application, server management	
Physical Characteristics	Dimension	142(L)* 85(W)* 14.5(H) mm	
Environment Conditions	Temperature	Operation	0~60°C
		Storage	-10~70°C
	Humidity	Operation	0~90%, Non-Condensed
		Storage	0~90%, Non-Condensed
Key Software			
Operating System		Microsoft Windows® CE .Net 6.0 Core version R3	
Navigation Software		Ndrive	
Maps	Provider	Tele Atlas and special	
Package Contents			
5" Unit * 1pc			
Mini USB cable * 1pc			
Stylus * 1pc			
Car charger * 1pc			
AC/DC adapter (Optional) * 1pc			
Bracket * 1pc			
Car mounting * 1pc			
User's manual * 1pc			
Gift box * 1pc			